

Lexmark T640



- Outstanding time to first page as fast as 6 seconds
- Value-priced, high-performance workgroup printer
- Broad range of paper-handling options
- Advanced user interface for easy operation

LEXMARKTM

Lexmark T640



- ImageQuick™ standard for fast graphic printing
- USB Direct interface for quick walk-up printing from USB flash memory drive
- Optional 802.11g wireless networking
- Numeric keypad for easy entry of confidential printing PINs

Lexmark T640, T640n, T640dn, T640tn, T640dtn


Product Specifications

Part Number¹	US/Canada: 20G0100 (T640), 20G0150 (T640n), 20G0130 (T640dn), 20G0400 (T640tn), 20G0500 (T640dtn)	
Product Class	Small workgroup laser printer	
Speed	Up to 35 ppm	
Resolution	1200 x 1200 dpi, 2400 image quality, 1200 image quality, 600 x 600 dpi	
Time to First Page	As fast as 6 seconds	
Processor	400 MHz	
Memory (std./max.)	64MB/576MB	
Connectivity		
Standard	T640: Parallel, USB, 1 internal solutions port (ISP), USB Direct Interface	
Optional	T640n, T640dn, T640tn, T640dtn: Ethernet, Parallel, USB, 1 ISP, USB Direct Interface	
Network Mgmt. Utility	T640: Ethernet, Gigabit Ethernet, Serial, Token-Ring, Coax/Twinax, Wireless, Fiber Optic T640n, T640dn, T640tn, T640dtn: Gigabit Ethernet, Serial, Token-Ring, Coax/Twinax, Wireless, Fiber Optic	
Operating Systems	Windows, Linux, UNIX, Mac, NetWare, and OS/400 For a complete list, visit www.lexmark.com.	
Printer Languages	PostScript 3 and PCL 6 emulations, PPDS Migration Tool	
Direct Print Formats	Base: PDF v1.5; Network: PDF v1.5, JPEG, JPG, TIFF, GIF, PNG, BMP, PCX and DCX	
Fonts	PCL: 89 scalable, 2 bitmapped. Includes OCR-A, OCR-B and Code 3 of 9 bar codes; PostScript: 158 scalable; PPDS: 39 scalable and 5 bitmapped	
Size (WxDxH)	T640, T640n: 16.6 in. x 19.6 in x 13.6 in. (421 mm x 498 mm x 345 mm) T640tn: 16.6 in. x 19.6 in x 18.9 in. (421 mm x 498 mm x 479 mm) T640dn: 16.6 in. x 25.1 in x 15.6 in. (421 mm x 638 mm x 396 mm) T640dtn: 16.6 in. x 25.1 in x 20.9 in. (421 mm x 638 mm x 530 mm)	
Weight	T640, T640n: 38 lb. (17.4 kg)	T640dn: 49 lb. (22.3 kg)
	T640tn: 45 lb. (20.2 kg)	T640dtn: 56 lb. (25.5 kg)
Acoustics	53 dBA printing; 30 dBA idle	
Duty Cycle	Up to 200,000 pages per month	
Warranty	1-year Advanced Exchange limited warranty	

Media Specifications

Paper Capacity (sheets)	T640, T640n, T640dn	T640tn, T640dtn
Standard Input	350 (250+100 MPT)	850 (250+500+100 MPT)
Maximum Input	3,850	3,850
Standard Output	250	250
Maximum Output	2,750	2,750
Paper Sources	T640, T640n, T640dn	T640tn, T640dtn
Standard Input	2	3
Maximum Input	7	7
Standard Output	1	1
Maximum Output	11	11
Media Types	Plain paper, bond, envelopes, card stock, transparencies, paper labels ³ , dual-web labels ³ , polyester labels ³ , vinyl labels ³	
Media Sizes	Letter, legal, A4, A5, JIS B5, statement, executive, folio, universal (2.75 x 5 in. to 8.5 x 14 in.), and envelopes (7 ³ / ₄ , 9, 10, DL, C5, B5, other)	
Media Weights	Plain paper: 16 to 47 lb. (60 to 176 g/m ²); Card stock: up to 110 lb. Index (199 g/m ²)	

In the Box



Lexmark T640

- Lexmark T640 Printer
- 6,000-page Return Program Print Cartridge²
- Power Cord
- Publications CD
- Drivers and Utilities CD

Lexmark T640n

- Lexmark T640 PLUS
- Ethernet

Lexmark T640dn

- Lexmark T640n PLUS
- 250-sheet duplex unit

Lexmark T640tn

- Lexmark T640n PLUS
- 500-sheet drawer

Lexmark T640dtn


- Lexmark T640tn PLUS
- 250-sheet duplex unit

Lexmark T640

Supplies & Accessories

Supplies	21,000-page High Yield Return Program Print Cartridge ²	64015HA ⁴
	21,000-page High Yield Print Cartridge ²	64035HA ⁴
	21,000-page High Yield Return Program Print Cartridge for Labels ²	64004HA ⁴
	6,000-page Return Program Print Cartridge ²	64015SA ⁴
	6,000-page Print Cartridge ²	64035SA ⁴
	Staple Cartridge	11K3188
	Routine Maintenance Item:	
	Maintenance Kit	40X0100
Memory/Flash Options	128MB DDR RAM	13N1523
	256MB DDR RAM	13N1524
	512MB DDR RAM	13N1526
	32MB Flash Card ⁵	1021208
	64MB Flash Card ⁵	1021209
	T64x Hard Drive	1021207
Furniture	Low Profile Printer Stand	16C0379
	Printer Stand with Cabinet	16C0369
	Printer Stand	16C0389
	T6xx Printer Base	10G0080

Paper Handling Options³



Additional Information

¹ Functions only with replacement cartridges designed for use in the USA and Canada

² Declared standard page yield value in accordance with ISO/IEC 19752

³ Printing label applications requires a special fuser cleaner included in the cartridge for labels

⁴ Designed for use only in the USA and Canada

⁵ One flash memory slot and one application slot available

⁶ Displays all available options for **base** model

⁷ Can staple a maximum of 25 sheets per set

⁸ Requires optional 500-sheet drawer

⁹ Requires optional 400-sheet universally adjustable drawer

¹⁰ Requires optional 250-sheet universally adjustable drawer

Options not pictured:

250-sheet Tray (20G0879)

500-sheet Tray (20G0884)⁸

250-sheet Universally Adjustable Drawer (20G1223)

250-sheet Universally Adjustable Tray (20G1224)¹⁰

400-sheet Universally Adjustable Drawer (20G1218)

400-sheet Universally Adjustable Tray (20G1217)⁹

T Horizontal Kiosk Presenter (11K4648)

T Vertical Kiosk Presenter (11K4647)

Lexmark T640

Additional Accessories

Connectivity	MarkNet X2000 Series External Print Servers ¹	
	X2011e Ethernet 10/100BaseTX	46D0060
	X2012e Ethernet 10/100BaseTX/10Base2	46D0040
	X2031e Ethernet 10/100BaseTX (3 ports)	46D0020
	X2030t Token-Ring (3 ports)	46D0000
	MarkNet N4000 Series External Print Servers ²	
	N4000e Ethernet 10/100BaseTX	14T0030
	MarkNet N8000 Series Internal Print Servers	
	N8000 Fast Ethernet	14S0230
	N8020 Gigabit Ethernet	14S0200
	N8030 Fiber 10/BaseFX	14S0220
	Wireless	
	N8050 802.11g Print Server	14S0165
	N4050e 802.11g Print Server ²	14T0145
802.11g Print Adapter	1010042	
Application Solutions	Bar Code Card	20G0737
	Card for IPDS and SCS/TNe	20G0738
	PrintCryption™ Card	20G0740
	Forms Card – Single Byte	20G0741
	Forms Card – Simplified Chinese	20G0742
	Card for PRESCRIBE	20G0739
	Korean Font Card	1021240
	Simplified Chinese Font Card	1021241
	Traditional Chinese Font Card	1021242
	Japanese Font Card	1021243
	Other Attachment Options	1284-B Parallel Card
RS-232C Serial Interface Card		11K4602
RS-232C/422C External Serial Adapter		1368705
Coax/Twinax Adapter for SCS		14S0240
Cable Options	Serial 50-foot Cable	1038693
	Parallel 6-foot 1284-C Cable	11K4078
	Parallel 1284 C-B Adapter	11K4250
	USB 6-foot Cable	12A2405
	Parallel 10-foot high speed bidirectional Cable	1329605
Print Media	Transparencies	70X7240

¹ Requires external parallel connection

² Requires USB connection

Lexmark and Lexmark with diamond design are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. PrintCryption and ImageQuick are trademarks of Lexmark International, Inc. Mac is a trademark of Apple Computer, Inc., registered in the U.S. and other countries. PCL is a registered trademark of Hewlett-Packard Company. The USB-IF logo is a trademark of Universal Serial Bus Implementers Forum, Inc. All other trademarks are the property of their respective owners. © 2005 Lexmark International, Inc. All rights reserved.

71K1100



Printed on recycled paper.

